

HYLOMAR RED SEMI-HARDENING JOINTING COMPOUND

Description 描述

Hylomar Red Semi-Hardening Jointing Compound allows for quick and easy dismantling for service and repair work to be carried out. The compound has excellent gap filling properties which makes it ideal for use on pitted, corroded or roughly machined surfaces.

Hylomar Red Semi-Hardening Jointing Compound 在维修作业中容易迅速地产生效果。该化合物具有优秀的填补间隙的特点，尤其适用于凹陷的、被腐蚀的或粗糙的加工表面。

Its chemical composition helps prevent corrosion between dissimilar metals. It is resistant to petrol, oil, steam, water & anti-freeze solutions and dilute acids such as battery acid.

该化合物能够抵御不同金属间的腐蚀。它能抵抗汽油、润滑油、蒸汽、水、防冻液和弱酸，如电池的酸。

Typical Properties 特性

Appearance 外观	Red Paste 红色-糊状
Specific Gravity 比重	1.4
Viscosity Spindle 6 @ 20 rpm 针入度	38000 cps @ 20°C
Temperature range 温度范围	-40° to +250°C
Volatile matter 挥发度	20%
Shelf Life 存放期	2 years in original unopened containers when stored between 5°C and 25°C 在 5°C-25°C 之间，未开封的条件下，存放期 2 年。

Directions for use 使用指南

Apply directly to surfaces previously cleaned, which are free from contamination such as rust, grit or grease. Once applied leave for a few minutes before closing joint. On threaded joints apply compound directly into threads taking care to ensure excess does not enter into fluid pipes or oilways. Clean any excess compound away with methylated spirits.

直接用于预先清洁的表面，去除污染物，如，锈、砂或油脂。涂布后等待分钟再合上结合面。如果是螺纹的结合面，小心确认多余的化合物没有进入液管或油路。用甲基的液体清除多余的化合物。

Typical Applications 典型运用

Hylomar Red Semi-Hardening Jointing Compound is recommended for use on aluminium and alloy cylinder heads etc. It is excellent on flanged and screwed joints.

Information given in this publication is based upon technical data gained in our own and other Laboratories and is believed to be true. However if the material is used in conditions beyond our control we can assume no liability for results obtained or damages incurred through the application of the data present herein.

Hylomar Ltd, Cale Lane, Wigan WN2 1JT UK Tel: +44 (0) 1942 617000 Fax: +44 (0) 1942 617001	Revision date	17 07 01	Page 1 of 2
	Product name	Hylomar Red Semi Hardening Jointing Compound	

Hylomar Red Semi-Hardening Jointing Compound 推荐运用于铝或合金的气缸盖等。它在平面和螺纹的结合面都有优秀的表现。

Handling and Safety Properties 操作和安全

Classification; Highly Flammable 分类, 高易燃

Risk phrase 危险术语= R11

Safety phrases 安全术语= S2, S7, & S16

Packaging 包装

Hylomar Red Semi-Hardening Jointing Compound is available in 100g tubes & 500 ml tins. For full details please contact our Sales Department.

Hylomar Red Semi-Hardening Jointing Compound 的包装为 100g tubes 和 500 ml tins。具体的信息, 请联系我们的销售部门。

Information given in this publication is based upon technical data gained in our own and other Laboratories and is believed to be true. However if the material is used in conditions beyond our control we can assume no liability for results obtained or damages incurred through the application of the data present herein.

Hylomar Ltd, Cale Lane, Wigan WN2 1JT UK Tel: +44 (0) 1942 617000 Fax: +44 (0) 1942 617001	Revision date	17 07 01	Page 2 of 2
	Product name	Hylomar Red Semi Hardening Jointing Compound	